USGS STM SENSOR RECOVERY FORM (one form per housing)

DATE: 9/01/12 **STORM:** ISAAC **INSPECTORS:** CJH

Housing #

SITE INFO

SITE ID: HWM-MS-HAR-010 independant **LAT** (DD to 6 places): 30.41926
(format: SSS-ST-COU-###PP; see SOP)

SITE NAME: Debris line near Airport Rd. **LONG** (DD to 6 places): 89.08721

STATE: MS **COUNTY:** HARRISON **Landowner Info: Notified** (Yes/No) **Name:**

SENSOR INFORMATION

Sensor Type (circle one):
Hobo Troll
RDG RDW
HWM
Other? _____
Serial # _____

Deployed as (circle one):
Water level (WL)
Baro Pressure (BP)
Wave Height (WV)
HWM
Other?

Data Interval:
30 sec 2 sec Other: _____
Sensor Deploy Time (GMT): _____
Data Start Time (GMT): _____
Sensor in Water (Y/N)

BP sensor collocated?
(Yes/No)
BP Site ID: _____
USGS VI on housing?
(Yes/No)

DETERMINE WATER SURFACE

Water Surface Reference Point (WSRP) Info

Reference Point (WSRP) # _____
HWM
~~WSRP~~ elevation (feet): 10.972
Elevation Assumed? *(Yes/No)*
WSRP description: Fair debris line stake marked with Nail and survey disk off Airport Rd. to left heading south on gravel Rd. towards Air strip South of 2nd chain link inclosed guidance beacon

Water Surface (WS) Elev. Calculations

TD Time: _____ GMT

WSRP elevation (WSRP):	_____ feet
Tapedown (A):	_____ feet
Weight length (B):	_____ feet
Total TD (A + B):	_____ feet
WS = WSRP – (A + B):	_____ feet

WS conditions (circle)? Calm Choppy Wavy



DETERMINE THE SENSOR HOUSING ELEVATION

To determine the Sensor Housing Elevation using a tapeup/tapedown from the established water surface elevation above, use the box to the right.

Choose option!

If elevation run to 2nd RP (SHRP) above sensor. then use lower boxes.

Sensor Housing Nut Elevation (D) from WS

Water Surface (WS):	_____ feet
Nut in water? Tape up to nut	_____ feet
OR	
Nut out of water? Tape down:	_____ feet
D = (WS +/- C) -S:	_____ feet



Sensor Housing RP Info

Reference Point (SHRP) # _____
SHRP elevation (feet): _____
Elevation Assumed? *(Yes/No)*
RP description:
_____
_____

Sensor Housing Nut Elevation (D) from SHRP

SHRP elevation:	_____ feet
Tapedown (A):	_____ feet
Weight length (B):	_____ feet
Total TD (A + B):	_____ feet
Subtract slippage (S):	_____ feet
D = SHRP – (A + B) - S:	_____ feet



Flip over to Page 2

USGS STM SENSOR RECOVERY FORM (page 2)

SENSOR ORIFICE ELEVATION

Sensor Orifice Elevation (G = D - E)

Housing Nut (D): _____ feet

Subtract Housing Correction Factor (E): _____ feet

Sensor Orifice Elevation (G):

_____ feet



SENSOR HEIGHT ABOVE GROUND

Use if Sensor Deployed Above Ground w/ no RP

Elevation (OEG=D-(H-E))

Housing Nut (D): _____ feet

TD to Ground (H): _____ feet

Subtract Housing Correction Factor (E): _____ feet

Data offset for Depth above Ground (OEG): _____ feet

This is used only until RP elevation is surveyed in to get initial estimate of depth above ground surface



DRAW SITE SKETCH BELOW



CHECK IN!!	Pictures Taken (circle all that apply): Sensor RP RM	North South East West
	Departure Time: _____ GMT Check-In Time: _____ GMT	STM Coord. on duty: _____